


General		
Shape	Free form / Square	
Seating Capacity	7	
Shell Material	Ultralife™ / Geloy®	
Dimensions	91¾" x 91¾" x 40" H / (233cm X 233cm x 102cm H)	
Corner Radii	22" (56 cm)	
Water Capacity	375 Gallons (1420 Liters)	
Dry Weight	1100 lbs (499 kg)	
Shipping Weight	Domestic 1100 lbs (499 kg) - Export 1150lbs (531 kg)	
Full Weight	4225 lbs (1917 kg)	
Skirt Material	Synthetic	
Poly Floor	Yes	
Water System		
Water Treatment System	Ultra Pure™	
Plumbing Systems	5	
Filters/Coverage	2 / 75 sq. ft.	
Gate Valves	6	
VCR Jet® - Air Adjustable/Directional	2	
VCR Jet® - Rotator	6	
VCR Jet® - Dual Rotator	0	
VCR Jet® - Multi Port Spinner	0	
VCR Jet® - Mini Rotator	22	
VCR Jet® - Mini Directional	4	
VCR Jet® - Euro Directional	12	
VCR Jet® - Euro Rotator	14	
VCR Jet® - Mini Directional in NFJ	8	
Typhoon Jet	1	
Ozone Jet	1	
Heater Return Jet	1	
Pump Returns	6	
Diverter Valves	2	
Floor Drains	1	
Skimmer	8" Weir	
Special Features		
Dynamic Massage Sequencer w/ control panel	Yes	
NeckFlex® Jet Pillows	2	
Headrest Pillows	4	
Stereo system	Optional Wireless*	
Water Feature	Yes	
Water Feature Volume control	Yes	
Cup Holders	4	
Tactile Therapy	Floor pedestal	
Under water magnetic switch	Yes	
Air Control Valve	No	
Pump Information		
	Domestic (60Hz)	Export (50Hz)
Motor Size – Peak (Continuous) HP	3.6 (2.0) HP	3.6 (2.0) HP
Jet Pumps # of Pumps/Speed	One / Dual & Two / Single	One / Dual & Two / Single
Circulation pump	1	1
Fountain pump	1	1
Electrical System		
	Domestic (60Hz)	Export (50Hz)
Voltage	240	240
Amperage	50/40	2X16 / 1X32 3X16
Heater	FastFlo 2.7,4.0,5.5 kW	FastFlo 3.3 kW 2.1, 5.2 kW
Thermostat	Electronic	Electronic
Light	2 Multi color LED	2 Multi color LED
Control System	MSPA-MP-D14	MSPA-MP-D12-CE
Upper Control	Scrolling Message Center	Scrolling Message Center
Auxiliary Upper Control	No	No
Programmable	Yes	Yes




* Wireless stereo not available for export

Note: 1. Subject to change without notice.

2006 Lotus Bay Architectural Specification



Top View Of Spa



Front View Of Spa

Caution:
Due to manufacturing tolerances there could be some minor differences between the actual spa and the drawing above. If site planning is critical to such tolerances, be sure to measure your actual spa.

- Note:**
1. Subject to change without notice.
 2. Engineering specs may differ slightly from brochure.
 3. For E-Z lifter installation allow 18" (45.72cm) clearances on the backside of the spa.
 4. Alternative cabinets may add significant weight. Ask your dealer for exact details